


Optilux

SPECIFICATIONS

ursa

FOR INFORMATION, CONTACT US_
INFO@URSALIGHTING.COM
TEL: +1 (510) 687-1128
URSALIGHTING.COM





FEATURES

- Advanced 3-PAD COB LED technology
- Mounting bracket with optional mounting hooks
- Passive Cooling Heatsink Technology
- Lighting Footprint : 4'x4'
- Waterproof, full IP65 rating
- Optimal Hang height 18-24 in.
- PPFD: Up to 1500 $\mu\text{mol}/\text{m}^2\text{s}$
- Power usage (actual draw) 638W

01

MECHANICAL SPECIFICATIONS




Dimensions (mm)	600 x 600 x 145 [195 w/ eyebolt]
Weight	46 lbs (20.8 kg)
Material	SPCC/Stainless Steel
Input Voltage	90 - 305 VAC Standard 347V (Option) 480V (Option)

Operation Temperature / Humidity & Storage Temp / Humidity

Working Temp.	-40 ~ +25 °C
Working Humidity	20 ~ 95% RH non-condensing
Storage Temp. Humidity	-40 ~ 85 °C, 10 ~ 95% RH

SPECTRUM GRAPH






PRODUCT CODE

OPTILUX640-W V4.0



02

PPFD MEASUREMENTS

4' X 4' SINGLE CANOPY DEMONSTRATION




4' X 16' SINGLE-ROW DEMONSTRATION (VERTICAL GROW)



02

PPFD MEASUREMENTS

12' X 16' LARGE CANOPY DEMONSTRATION (COMMERCIAL ROOM)



IDEAL FIXTURE ARRANGEMENT

